















XMN1P/9180A EN ISO 20344:2022+A1:2024 EN ISO 20347:2022+A1:2024

# **mid**liteX

### **SOLIDGRIP**

## **FEATURES**

- anti-static
- cut resistant
- ladder grip in sole for extra security
- robust, yet lightweight
- excellent grip, even on wet and greasy surfaces (SRC certified)
- easy on & off thanks to kick-off spur
- resistant to fats, manure and a variety of chemicals


















#### Size chart

#### EU 36 - 49 | UK 3.5 - 15 | US 4 - 16





Please add an extra 1 cm / 0.4 inch for extra comfort or when wearing thick socks.

Size EU	Size UK	Size US	A. Length Of The Last		B. Shaft height		C. Shaft Circumference	
			mm	inch	mm	inch	mm	inch
36	3.5	4	241	9.49	205	8.07	350	13.78
37	4	5	247	9.72	205	8.07	360	14.17
38	5	5.5	253	9.96	210	8.27	370	14.57
39	6	6	260	10.24	220	8.66	380	14.96
40	6.5	7	267	10.51	225	8.86	390	15.35
41	7	8	273	10.75	230	9.06	390	15.35
42	8	9	280	11.02	230	9.06	400	15.75
43	9	10	287	11.30	235	9.25	410	16.14
44	10	11	294	11.57	240	9.45	410	16.14
45	10.5	12	300	11.81	245	9.65	420	16.54
46	11	13	307	12.09	245	9.65	430	16.93
47	12	14	314	12.36	250	9.84	440	17.32
48	13	15	320	12.60	250	9.84	440	17.32
49	14	16	327	12.87	255	10.04	450	17.72





